
MSR Gold™ FastFit



MSR Gold™ FastFit



Α	В	C	D	E	
25	4	65	111	41	
26	5	65	128	41	
		25 4 26 5	25 4 65	25 4 65 111	25 4 65 111 41

Dimensions in mm

Features

- I. Philips FastFit.
- 2. Very short arc.
- 3. Compact design.
- 4. Flexible power range.
- 5. Philips pinch protection.
- 6. Innovative gold plated pins.
- 7. MSR filling.

Benefits

- 1. Lamp replacement in just seconds, exchangeable with halogen lamp.
- 2. High beam intensity.
- 3. Easy handling, Smaller and lighter fixtures possible.
- 4. Boostable light levels.
- 5. Enables use at higher temperatures in any burning position. Longer lifetime, fewer early failures, consistent performance over time.
- 6. Reduces early lamp or lamp holder failures. Excellent current transfer.
- 7. Pure, white light; color point close to black body line.

Application

• Entertainment.

Туре	Lamp wattage	Cap/ base	Arc size	Minimum ignition supply voltage	Lumen output	Efficacy source	Colour temp.
			mm			lm/W	
MSR Gold 700 FastFit	700 W ¹	PGJX50 (FastFit)	4	207 V	50.000 lm	75	7500 K
MSR Gold 1200 FastFit	1200 W ²	PGJX50 (FastFit)	5	207 V	95.000 lm	80	6300 K

Туре	Max. perm. pinch temp $^{\circ}$ \subset	CRI	Average life h	Replacement before hrs	Burning position	Lamp current A	Ordering number
MSR Gold 700 FastFit	500	> 80	750	850	Any	10	9281 748 05108
MSR Gold 1200 FastFit	500	> 80	750	850	Any	13	9281 750 05108

¹⁾ Lamp can be operated between 400 and 800W. At 400W for max. 50% of its lifetime.

Dealer stamp

²) Lamp can be operated between 600 and 1400W. At 600W for max. 50% of its lifetime.